

# panax color UK SEUNG CHEMICAL Co. LTD

# **PANAX RED 2RL**

## PRODUCT DESCRIPTION

**Color Index** Pigment Red 48:3

C.I. No. 15865:3

**Chemical Type** BONA pigment lakes (Sr-Salt)

CAS No. 15782-05-5 **EINECS No.** 239-879-2

## PHYSICAL DATA

| Appearance       | Red powder |                        |            |
|------------------|------------|------------------------|------------|
| pH (2% aqueous)  | 6-8        |                        | ISO 787-9  |
| Specific gravity | 1,7        | g/cm <sup>3</sup>      | ISO 787-10 |
| Bulk volume      | 530        | cm <sup>3</sup> /100 g | ISO 787-11 |
| Oil absorption   | 32         | g/100 g                | ISO 787-5  |

# **FASTNESS PROPERTIES**

| 3 | ISO 787-4                            |
|---|--------------------------------------|
| 2 | ISO 787-4                            |
| 5 | ISO 2836                             |
| 3 | ISO 2836                             |
| 4 | ISO 2836                             |
| 4 | ISO 2836                             |
| 4 | ISO 2836                             |
| 5 | ISO 787-21                           |
| 5 | ISO 787-21                           |
| 6 | ISO 105-B01                          |
| 5 | ISO 105-B01                          |
|   | 2<br>5<br>3<br>4<br>4<br>4<br>5<br>5 |


#### STANDARD PACKAGING

Paper bags 10 kg net Big Bags type C On request Revision date: 03/2014

**FULL SHADE** 

Revision No.: 3

REDUCTION 1:25 TiO<sub>2</sub>



## CHEMICAL STRUCTURE OF THE PIGMENT

$$O = C$$
 $O = C$ 
 $O =$ 

Molecular formulae  $C_{18}H_{11}CIN_2O_6S.Sr$ 

**Molecular Mass** 506,4 g/mol

## **APPLICATION RECOMMENDATION**

**Publication gravure** 

Water base flexo recommended

Offset

**Plastics** recommended

#### **REGULATORY COMPLIANCE**

German BfR IX

AP(89)1

FDA 21 CFR 178.3297 Not listed

**CONEG, EC 94/62** ROHS 2002/95/EC, 2005/618/EC

Our product specific end application information are based upon our current knowledge. They are presented without any representation or warranty concerning the suitability, performance or correctness of the product for a particular application or use. Significant variations can occur between test results and results obtained in actual use. We strongly advise that the customer test the product in the specific intended application under conditions expected during use.

#### **HEAD-OFFICE**

174, Gaejwa Ro, GEUMJEONG-GU 609-845 BUSAN, KOREA

Tel.: +82 51 523 1515 Fax: +82 51 523 7272 Email: trade@ukseung.co.kr http://www.ukseung.co.kr

## **EUROPE OFFICE**

UK SEUNG Europe GmbH Hauptstrasse 14 D-63860 Rothenbuch, Germany Tel.: +49 6094 9897426 Fax: +49 6094 9897427 Email: info@ukseung-europe.de http://www.ukseung-europe.de